

Registry

- [Registry Edit](#)

Registry Edit

REG ADD

REG DELETE

HKCR	HKEY_CLASSES_ROOT
HKCU	HKEY_CURRENT_USER
HKLM	HKEY_LOCAL_MACHINE
HKU	HKEY_USERS
HKCC	HKEY_CURRENT_CONFIG

Example of how to change your homepage:

```
REG ADD "HKCU\Software\Microsoft\Internet Explorer\Main" /v "Start Page" /d http://my.yahoo.com /f
```

Disable AutoPlay (XP)

```
REG ADD "HKLM\Software\Microsoft\Windows\CurrentVersion\Policies\Explorer" /v NoDriveTypeAutoRun /t REG_DWORD /d 255 /f
```

```
REG ADD "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\LanguagePack" /v UniScribe /t REG_DWORD /d 2
```

Meltdown registry

```
REG ADD "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\QualityCompat" /v cadca5fe-87d3-4b96-b7fb-a231484277cc /t REG_DWORD /d 0x00000000
```

REG Operation [Parameter List]

```
Operation [ QUERY | ADD | DELETE | COPY |  
          SAVE | LOAD | UNLOAD | RESTORE |  
          COMPARE | EXPORT | IMPORT | FLAGS ]
```

Return Code: (Except for REG COMPARE)

0 - Successful

1 - Failed

For help on a specific operation type:

```
REG ADD KeyName [/v ValueName | /ve] [/t Type] [/s Separator] [/d Data] [/f]
```

KeyName [[\\Machine\FullKey](#)]

Machine Name of remote machine - omitting defaults to the

current machine. Only HKLM and HKU are available on remote machines.

FullKey ROOTKEY\SubKey

ROOTKEY [HKLM | HKCU | HKCR | HKU | HKCC]

SubKey The full name of a registry key under the selected ROOTKEY.

/v The value name, under the selected Key, to add.

/ve adds an empty value name (Default) for the key.

/t RegKey data types

[REG_SZ | REG_MULTI_SZ | REG_EXPAND_SZ |

REG_DWORD | REG_QWORD | REG_BINARY | REG_NONE]

If omitted, REG_SZ is assumed.

/s Specify one character that you use as the separator in your data

string for REG_MULTI_SZ. If omitted, use "\0" as the separator.

/d The data to assign to the registry ValueName being added.

/f Force overwriting the existing registry entry without prompt.

Examples:

```
REG ADD \\ABC\HKLM\Software\MyCo
```

Adds a key HKLM\Software\MyCo on remote machine ABC

```
REG ADD HKLM\Software\MyCo /v Data /t REG_BINARY /d fe340ead
```

Adds a value (name: Data, type: REG_BINARY, data: fe340ead)

```
REG ADD HKLM\Software\MyCo /v MRU /t REG_MULTI_SZ /d fax\0mail
```

Adds a value (name: MRU, type: REG_MULTI_SZ, data: fax\0mail\0\0)

```
REG ADD HKLM\Software\MyCo /v Path /t REG_EXPAND_SZ /d ^%systemroot^%
```

Adds a value (name: Path, type: REG_EXPAND_SZ, data: %systemroot%)

Notice: Use the caret symbol (^) inside the expand string

```
REG DELETE KeyName [/v ValueName | /ve | /va] [/f]
```

KeyName [\[\\Machine\\]FullKey](#)

Machine Name of remote machine - omitting defaults to the current machine.

Only HKLM and HKU are available on remote machines.

FullKey ROOTKEY\SubKey

ROOTKEY [HKLM | HKCU | HKCR | HKU | HKCC]

SubKey The full name of a registry key under the selected ROOTKEY.

ValueName The value name, under the selected Key, to delete.

When omitted, all subkeys and values under the Key are deleted.

/ve delete the value of empty value name (Default).

/va delete all values under this key.

/f Forces the deletion without prompt.

Examples:

```
REG DELETE HKLM\Software\MyCo\MyApp\Timeout
```

Deletes the registry key Timeout and its all subkeys and values

```
REG DELETE \\ZODIAC\HKLM\Software\MyCo /v MTU
```

Deletes the registry value MTU under MyCo on ZODIAC